



SANITARY SEWER SERVICE: CUSTOMER PORTION

N.T.S.

NOTES:

1. ALL CONNECTIONS SHALL BE GASKETED.
2. TRACER WIRE SHALL BE MADE CONTINUOUS FROM THE CLEANOUT TO THE BASEMENT OR CRAWL SPACE. CUSTOMER TO CONNECT TO TRACING WIRE AT THE POINT OF CONNECTION NEAR THE CLEANOUT.
3. MAINTENANCE OF THE SEWER SERVICE FROM THE RIGHT-OF-WAY TO AND INCLUDING THE INTERNAL PLUMBING ON PREMISES, AND ITS USE, MUST ALWAYS BE KEPT IN FULL COMPLIANCE. THE FOREGOING REMAINS THE SOLE RESPONSIBILITY OF THE SEWER CUSTOMER.
4. THE CUSTOMER MUST SUBMIT A COMPLETED SEWER CONNECTION APPLICATION, OBTAIN TOWN APPROVAL TO PROCEED AND SCHEDULE INSPECTIONS BY THE TOWN PRIOR TO BACKFILLING OR PLACING THE CUSTOMER PORTION INTO USE.
5. A LARGER DIAMETER SERVICE LINE MAY BE REQUIRED WHERE DISTANCE OR CONSUMER DEMAND ARE A FACTOR.
6. CUSTOMER SHALL INSTALL CLEANOUTS, PER DETAIL S-06, AT 100' INTERVALS AS REQUIRED.
7. REFER TO MATERIAL LIST, S-03.

ISSUE DATE: JUNE 2015		TOWN OF BATAVIA
REVISIONS	DATE	COMMENTS
		SANITARY SEWER DETAILS SANITARY SEWER SERVICE: CUSTOMER PORTION
		DRAWING S-04C